

## 5 PIN DIP RANDOM-PHASE TRIAC DRIVER PHOTOCOUPLER

**EL305X(P5)(JY) Series**

### Features:

- Peak breakdown voltage
  - 250V: EL301X(P5)
  - 400V: EL302X(P5)
  - 600V: EL305X(P5)
- High isolation voltage between input and output (Viso=5000 V rms )
- Compact dual-in-line package
- Pb free and RoHS compliant.
- UL approved (No. E214129)
- VDE approved (No.132249)
- SEMKO approved
- NEMKO approved
- DEMKO approved
- FIMKO approved
- CSA approved
- CQC approved

### Description


The EL301X(P5), EL302X(P5) and EL305X(P5) series of devices each consist of a GaAs infrared emitting diode optically coupled to a monolithic silicon random phase photo Triac.

They are designed for interfacing between electronic controls and power triacs to control resistive and inductive loads for 115 to 240 VAC operations.


.

### Applications

- Solenoid/valve controls
- Lamp ballasts
- Static AC power switch
- Interfacing microprocessors to 115 to 240Vac peripherals
- Incandescent lamp dimmers
- Temperature controls
- Motor controls



Schematic



Pin Configuration

1. Anode
2. Cathode
3. No Connection
4. Terminal
5. Pin Cut
6. Terminal

# 5 PIN DIP RANDOM-PHASE TRIAC DRIVER PHOTOCOUPLER

## EL305X(P5)(JY) Series

### Absolute Maximum Ratings (T<sub>a</sub>=25°C)

Parameter			Symbol	Rating	Unit
Input	Forward current		I <sub>F</sub>	60	mA
	Reverse voltage		V <sub>R</sub>	6	V
	Power dissipation		P <sub>D</sub>	100	mW
	Derating factor (above 85°C)			3.8	mW /°C
Output	Off-state Output Terminal Voltage	EL301X	V <sub>DRM</sub>	250	V
		EL302X		400	
		EL305X		600	
	Peak Repetitive Surge Current		I <sub>TSM</sub>	1	A
	Power dissipation		P <sub>D</sub>	300	mW
	Derating factor (above 85°C)			7.4	mW /°C
Isolation voltage <sup>*1</sup>			V <sub>iso</sub>	5000	V rms
Total power dissipation			P <sub>D</sub>	330	mW
Operating temperature			T <sub>opr</sub>	-55~+100	°C
Storage temperature			T <sub>stg</sub>	-55~+125	°C
Soldering temperature <sup>*2</sup>			T <sub>sol</sub>	260	°C

### Notes

\*1 AC for 1 minute, R.H.= 40 ~ 60% R.H. In this test, pins 1, 2 & 3 are shorted together, and pins 4, 5 & 6 are shorted together.

\*2 For 10 seconds.

# 5 PIN DIP RANDOM-PHASE TRIAC DRIVER PHOTOCOUPLER

## EL305X(P5)(JY) Series

Electrical Characteristics ( $T_a=25^{\circ}\text{C}$  unless specified otherwise)

### Input

Parameter	Symbol	Min.	Typ.*	Max.	Unit	Condition
Forward voltage	$V_F$	-	1.18	1.5	V	$I_F = 10\text{mA}$
Reverse Leakage current	$I_R$	-	-	10	$\mu\text{A}$	$V_R = 6\text{V}$

### Output

Parameter	Symbol	Min.	Typ.*	Max.	Unit	Condition
Peak Blocking Current	$I_{\text{DRM}}$	-	-	100	nA	$V_{\text{DRM}} = \text{Rated } V_{\text{DRM}}$ $I_F = 0\text{mA}$
Peak On-state Voltage	$V_{\text{TM}}$	-	-	2.5	V	$I_{\text{TM}}=100\text{mA peak}$ , $I_F=\text{Rated } I_{\text{FT}}$
Critical Rate of Rise off-state Voltage	EL301X EL302X	$dv/dt$	100	-	$\text{V}/\mu\text{s}$	$V_{\text{PEAK}} = \text{Rated } V_{\text{DRM}}$ , $I_F=0$ (Fig. 8)
	EL305X					$V_{\text{PEAK}} = 400\text{V}$ , $I_F=0$ (Fig. 8)

### Transfer Characteristics

Parameter	Symbol	Min.	Typ.*	Max.	Unit	Condition
LED Trigger Current	EL3010 EL3021 EL3051	-	-	15	mA	Main terminal Voltage=3V
	EL3011 EL3022 EL3052	-	-	10		
	EL3012 EL3023 EL3053	-	-	5		
Holding Current	$I_H$	-	250	-	$\mu\text{A}$	


\* Typical values at  $T_a = 25^{\circ}\text{C}$

# 5 PIN DIP RANDOM-PHASE TRIAC DRIVER PHOTOCOUPLER


**EL305X(P5)(JY) Series**

## Typical Performance Curves


**Figure 1. Forward Current vs Forward Voltage**




**Figure 2. On-State Characteristics**




**Figure 3. Holding Current vs. Ambient Temperature**




**Figure 4. LED Current Required to Trigger vs. LED Pulse Width**




**Figure 5. Leakage Current vs. Ambient Temperature**




**Figure 6. LED Trigger Current vs. Ambient Temperature**



# 5 PIN DIP RANDOM-PHASE TRIAC DRIVER PHOTOCOUPLER EL305X(P5)(JY) Series



**Figure 8. Static dv/dt Test Circuit & Waveform**



## Measurement Method

The high voltage pulse is set to the required  $V_{PEAK}$  value and applied to the D.U.T. output side through the RC circuit above. LED current is not applied. The waveform  $V_T$  is monitored using a x100 scope probe. By varying  $R_{TEST}$ , the dv/dt (slope) is increased, until the D.U.T. is observed to trigger (waveform collapses). The dv/dt is then decreased until the D.U.T. stops triggering. At this point,  $\tau_{RC}$  is recorded and the dv/dt calculated.

$$dv/dt = \frac{0.632 \times V_{PEAK}}{\tau_{RC}}$$

## 5 PIN DIP RANDOM-PHASE TRIAC DRIVER PHOTOCOUPLER

**EL305X(P5)(JY) Series**

For example,  $V_{PEAK} = 400V$  for EL302X series. The dv/dt value is calculated as follows:

$$dv/dt = \frac{0.63 \times 400}{\tau_{RC}} = \frac{252}{\tau_{RC}}$$

### Order Information

#### Part Number

**EL301XY(Z)(P5)-V**  
or **EL302XY(Z)(P5)-V**  
or **EL305XY(Z)(P5)-V**

#### Note


X = Part No. for EL301x (0, 1 or 2)  
X = Part No. for EL302x, EL305x (1, 2 or 3)  
Y = Lead form option (S, S1, M or none)  
Z = Tape and reel option (TA, TB or none).  
P5 = 5 pins type  
V = VDE safety approved (optional)

Option	Description	Packing quantity
None	Standard DIP-6	65 units per tube
M	Wide lead bend (0.4 inch spacing)	65 units per tube
S (TA)	Surface mount lead form + TA tape & reel option	1000 units per reel
S (TB)	Surface mount lead form + TB tape & reel option	1000 units per reel
S1 (TA)	Surface mount lead form (low profile) + TA tape & reel option	1000 units per reel
S1 (TB)	Surface mount lead form (low profile) + TB tape & reel option	1000 units per reel


# 5 PIN DIP RANDOM-PHASE TRIAC DRIVER PHOTOCOUPLER EL305X(P5)(JY) Series

## Package Drawings (Dimensions in mm)

### Standard DIP Type




### Option M Type




# 5 PIN DIP RANDOM-PHASE TRIAC DRIVER PHOTOCOUPLER EL305X(P5)(JY) Series

## Option S Type



## Option S1 Type







# 5 PIN DIP RANDOM-PHASE TRIAC DRIVER PHOTOCOUPLER

**EL305X(P5)(JY) Series**

Recommended pad layout for surface mount leadform



## Device Marking




### Notes

EL denotes Everlight  
3053 denotes Device Number  
Y denotes 1 digit Year code  
WW denotes 2 digit Week code  
V denotes VDE optional


# 5 PIN DIP RANDOM-PHASE TRIAC DRIVER PHOTOCOUPLER

EL305X(P5)(JY) Series

## Tape & Reel Packing Specifications



## Tape dimensions




Dimension No.	A	B	D0	D1	E	F
Dimension (mm)	10.4±0.1	7.52±0.1	1.5+0.1/-0	1.5+0.1/-0	1.75±0.1	7.5±0.1

Dimension No.	P0	P1	P2	t	W	K
Dimension (mm)	4.0±0.15	1.6±0.1	2.0±0.1	0.35±0.03	16.0±0.2	4.5±0.1

**5 PIN DIP RANDOM-PHASE TRIAC DRIVER  
PHOTOCOUPLER**

**EL305X(P5)(JY) Series**

**Solder Reflow Temperature Profile**



## **5 PIN DIP RANDOM-PHASE TRIAC DRIVER PHOTOCOUPLER**

### **EL305X(P5)(JY) Series**

---

#### **DISCLAIMER**

1. Above specification may be changed without notice. EVERLIGHT will reserve authority on material change for above specification.
2. When using this product, please observe the absolute maximum ratings and the instructions for use outlined in these specification sheets. EVERLIGHT assumes no responsibility for any damage resulting from use of the product which does not comply with the absolute maximum ratings and the instructions included in these specification sheets.
3. These specification sheets include materials protected under copyright of EVERLIGHT. Reproduction in any form is prohibited without the specific consent of EVERLIGHT.